



AZZA Digital Signage 115"

Model : 115BA3K

LCD Monitor A professional LCD monitor designed to deliver clear, sharp, and detailed images. It features a high-quality LCD panel with excellent color reproduction and wide viewing angles, making it suitable for office work, multimedia applications, presentations, and general-purpose display requirements.



Non-Glare Screen
Reduces glare for clear and comfortable viewing.



Local Dimming
Enhances contrast with precise backlight control.



IP5X Dust Resistant
Dust-resistant protection for reliable operation.



30-Degree Tilting
Allows the screen to tilt up or down by up to 30° for a more comfortable viewing angle.



Wireless Screen Sharing
Enables wireless sharing of content from compatible devices to the display without using cables.



Android 16.0
for a smooth, secure, and intuitive user experience.

Display	
Model	115BA3K
LCD Size	115"
Panel type	TFT Ultra HD
Backlight	D-LED
Resolution	3840 x 2160 (pixels)
Screen Orientation	Landscape&Portrait
Brightness	500nits
Contrast Ratio	7000:1
Viewing Angle	178°[H]/178°[V]
Frame rate	120Hz
Response Time	6.5ms
Display Colors	1.07G (8bit+Hi-FRC)
Backlight Uniformity	80%
Haze	25%
Color Gamut (X% NTSC)	72%
MTBF	50,000 hrs
View area	2534.4[H]x1425.6[V]mm
Display Colors	1.07G(8bits+FRC)

Interface	
USB 2.0 x1	USB2.0 Type-A
USB 3.0 x1	USB3.0 Type-A
Type-C x1	Supports DP1.23840×2160@60HzIn +PD65W
HDMI IN x3	Support ARC.
HDMI OUT x1	3840*2160 @60Hz
AUDIO OUT x1	3.5mm mini interface
IR IN x1	3.5mm mini interface
S/PDIF OUT x1	Maxspeed : 16Mbps
RS232 IN x1	RJ-45
RS232 OUT x1	RJ-45
LAN IN x1	10M/100M/1000M (Interface) : RJ-45

Accessories	
Remote Control	X1
Power Cord(1.5M)	X1
Warranty Card	X1
Wall Mount	X1

Mother board	
CPU	Octa Core = A72*4 + A53*4 , Max 2.2GHz
GPU	Mali-G52 MC3
RAM / ROM	4GB / 64GB
OS	Android 16.0

Audio Output Power	
Standard	Speaker : 8Ω /20W*2

Language	
Language	English / Chinese Other 20 languages

Environment	
Working Temperature	0°C ~ 40°C
Storage Temperature	Minus 10°C ~ 60°C
Working Humidity	20% ~ 80% RH Non-Condensing
Storage Humidity	10% ~ 80% RH Non-Condensing
MAX working time (Hour/Day)	The longest service time 24 Hours × 7 days

Structure	
Product Size (W x D x H)	2570x70x1465mm
Package Size (W x D x H)	2740×225×1610mm
N.W	95±1.5Kg
Case Material	Metal face frame, sheet metal rear shell, all-metal structure. Anti-fire Military grade
VESA	4-M8 Screw Hole 1000mmx800mm

Power	
Voltage	100 V ~ 240 V/AC, 50/60 Hz
Maximum (Watt)	<570W

Optional Module	
OPS 80PIN	80PIN HDM IN 2.1